

# ABESCA H120 FAST



## ABESCA H120 FAST- H4b – W2

### SINGLE LINE BARRIER FOR CENTRAL RESERVE AND SIDE EDGE

Concrete road safety barrier 1.20 m high, H4b containment level.

Placed on asphalt and pinned by 6 anchoring "pins" with reduced insertion, easily removable and inspectable.

FAST connection system allows quick installation, easy removable and replacement in case of impact.



TECHNICAL FEATURES	H120 FAST – H4b – W2
<b>BARRIER</b>	H120 FAST
<b>LENGTH</b>	5.99 m
<b>HEIGHT</b>	120 cm
<b>BASE</b>	66 cm
<b>WEIGHT</b>	4900 kg
<b>ANCHORED BARRIER</b>	✓
<b>ANCHORED TERMINALS</b>	✓
<b>CE CERTIFICATION</b>	✓
CRASH TEST - EN 1317	H120 FAST – H4b – W2
<b>ASI</b>	B
<b>CONTAINMENT LEVEL</b>	H4b
<b>NORMALIZED WORKING WIDTH</b>	W2
<b>NORMALIZED DYNAMIC DEFLECTION</b>	0.4 m
<b>NORMALIZED VEHICLE INTRUSION</b>	VI7
<b>TEST LENGTH (EXCLUDING TERMINAL)</b>	72 m